


# **Noise Mapping Results**

# Report

January 16, 2025

## Noise Map - Noise map height 1.5m (A-weighted)



### **Model Overview**




# **Receiver Results - Summary**


Receiver Name	Height (m)	Total dB(A)	63Hz	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	8kHz
Receiver	2	42				42				
Receiver-2	2	40				40				
Receiver-3	2	39				39				
Receiver-4	2	40				40				
Receiver-5	2	45				45				
Receiver-6	2	41				41				
Receiver-7	2	43				43				


# Sources


Source Name	Height (m)	Total dB	63Hz	125Hz	250Hz	500Hz	1kHz	2kHz	4kHz	8kHz
Line	1	60				60				
Line-2	1	60				60				
Line-3	1	60				60				
Line-4	1	60				60				

#### **Receiver Locations**











Receiver

Receiver-2

Receiver-3

Receiver-4

Receiver-5







Receiver-6


Receiver-7


#### **Receiver Charts**


#### Receiver Results Chart dB(A)
























Receiver - Analysis of Sources Chart dB(A)










Receiver-2 - Analysis of Sources Chart dB(A)










Receiver-3 - Analysis of Sources Chart dB(A)










Receiver-4 - Analysis of Sources Chart dB(A)










Receiver-5 - Analysis of Sources Chart dB(A)










Receiver-6 - Analysis of Sources Chart dB(A)









Receiver-7 - Analysis of Sources Chart dB(A)







#### Configuration

Calculation Method ISO96132:2024 (New)

Hard Ground (Ground Factor = 0)

15.0°C Temperature

70% Humidity

Results are A-weighted

Results are rounded to 0 decimal places

Second order reflections are included

Reflections are only considered at a distance of 1m or greater from a reflector (facade level)

ISO9613-2 barrier attenuation limit (20/25dB) is enabled

Vertical edges (lateral paths) are included

Limited to convex paths

Following ISO17534-3 recommendation 5.2

Ground reflections are not screened (as recommended in ISO17534-3 5.3)

#### References

ISO 9613-1:1993 — Attenuation of sound during propagation outdoors — Part 1: Calculation of the absorption of sound by the atmosphere

ISO 9613-2:2024 — Attenuation of sound during propagation outdoors — Part 2: Engineering method for the prediction of sound pressure levels outdoors

ISO/TR 17534-3:2015 — Acoustics — Software for the calculation of sound outdoors — Part 3: Recommendations for quality assured implementation of ISO 9613-2 in software according to ISO 17534-1. Quality Assurance and Test Cases: https://dbmap.net/iso17534results